


- Semi-automatic test fixture with parallel vertical closing
- From small to large production capacity
- Kit mounted in the fixture, non-removable, ESD version
- High mechanical precision and pneumatic power
- Adjustable closing / opening strength (3 positions)



General Description

Product group	Test Fixture
Serie	UPe
Chamber's type	NS
Movement's type	HA
Standard size reference	2
Exchangeable Kit	No, but adaptable on option
Contact stroke generation	Pneumatic
Fixture's type	Pressor

Dimensions and Strokes

Outer dimensions open (WxDxH)	495 x 582 x 610 mm
Outer dimensions closed (WxDxH):	495 x 582 x 296 mm
Useable area	240 x 300 mm
Pushrod length	75 mm
Parallel contacting stroke	14,3 mm
Product support plate thickness	4 mm
Product support plate stroke	9,5 mm
Rear Plate Usable area	430 x 115 mm
Rear Plate Thickness	4 mm
Wiring plate dimensions (WxDxH)	455 x 400 x 6 mm

Energy and Power

Pneumatic requirement	6 bars
Max. contact force	1620 N
Input Diameter	6 mm
Solenoid Valve Voltage	24 VDC

ESD and Ground Connections

ESD UUT Support	Yes
Snap Button GND Connection	Yes
Banana Plug GND Connection	Yes
Frame Resistance to GND	< 2 Ω

Additional Features

Bottom contacting	Yes
Top contacting	Yes
Radio frequency version	On Option
Opening angle	60°
Housing angle	5°
Weight	18,6 kg
Min. Temperature	+10°C
Max. Temperature	+60°C
CE Certification compliant	Yes
Max. production capacity	100,000 pcs / month
Identification Plate	Yes
Closing Detection Switch	Yes
Second Detection Switch (Security Relay)	On demand

Reference Builder

ARF-UPe-P-NSHA2-P&P

Range

QLe	Quick Line range - Low volumes
UPe	Top Line range - All volumes

Type

D	Dedicated to debugging and labs
P	Dedicated to mass production

Radiofrequency version

NS	No Shielding Box
S	Shielding -80dB - 100MHz to 6GHz
SL	Shielding -100dB - 100MHz to 6GHz

Special

P&P	Plug&Play with exchangeable kit
-----	---------------------------------

Size

1	Usable width up to 150 mm
2	Usable width up to 250 mm
3	Usable width up to 440 mm

Operation

M	Manual
ML	Manual Lateral Contacting
HA	Semi-Automatic (Manual closing, automatic opening)
FA	Fully-Automatic
FAL	Fully-Automatic Lateral Contacting

ARF TEST SAS

30 Chemin du Vieux Chêne
38240 MEYLAN – France
+33 476 928 110
info@arf-test.com

www.arf-test.com